

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION OF CHEMICAL PRODUCT AND COMPANY

Substance:	Inorganic salt.
Trade Name:	Poolgard Knockout
Other Names:	Calcium Hypochlorite – hydrated, Dry Chlorine, Cal Hypo, Calcium oxychloride
Product Use:	Pool chlorination product.
Creation Date:	April, 2009
Revision Date:	September, 2010

SECTION 2 - HAZARDS IDENTIFICATION

Statement of Hazardous Nature

This product is classified as: Xn, Harmful. N, Dangerous to the environment. C, Corrosive. Hazardous according to the criteria of ASCC.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

Risk Phrases: R8, R31, R34, R50, R20/22. Contact with combustible material may cause fire. Contact with acids liberates toxic gas. Causes burns. Very toxic to aquatic organisms. Harmful by inhalation and if swallowed.

Safety Phrases: S22, S26, S28, S45, S46, S61, S1/2, S24/25, S36/37/39. Do not breathe dust. In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre. After contact with skin, wash immediately with plenty of water. In case of accident or if you feel unwell, contact a doctor or Poisons Information Centre immediately (show this MSDS where possible). If swallowed, contact a doctor or Poisons Information Centre immediately and show this MSDS or label. Avoid release to the environment. Refer to special instructions/Safety Data Sheets. Keep locked up and out of reach of children. Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection.

SUSDP Classification: S6

ADG Classification: Class 5.1: Oxidising Agents.

UN Number: 2880, CALCIUM HYPOCHLORITE, HYDRATED

Emergency Overview

Physical Description & colour: White granular solid.

Odour: Chlorine odour.

Major Health Hazards: causes burns, harmful by inhalation and if swallowed.

Potential Health Effects

Inhalation:

Short term exposure: Available data shows that this product is harmful, but symptoms are not available. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short term exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product is corrosive to the skin. Capable of causing moderate to severe burns with ulceration. Can penetrate to deeper layers of skin, resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure. Burns may not be immediately painful; the onset of pain may be minutes to hours.

Long Term exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short term exposure: This product is corrosive to eyes. It will cause severe pain, and corrosion of the eye and surrounding facial tissues. Unless exposure is quickly treated, permanent blindness and facial scarring is likely.

Long Term exposure: No data for health effects associated with long term eye exposure.

MATERIAL SAFETY DATA SHEET

Ingestion:

Short term exposure: Significant oral exposure is considered to be unlikely. Available data shows that this product is harmful, but symptoms are not available. However, this product is corrosive to the gastrointestinal tract. Capable of causing moderate to severe burns with ulceration. Can penetrate to deeper layers of skin, resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure.

Long Term exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

ASCC: No significant ingredient is classified as carcinogenic by ASCC.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Calcium hypochlorite	7778-54-3	70	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The ASCC TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

SECTION 4 - FIRST AID MEASURES

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Quickly and gently brush away excess solids. Seek immediate medical attention. Flush contaminated area with lukewarm, gently flowing water for at least 20-30 minutes, by the clock. If irritation persists, repeat flushing.

Eye Contact: Quickly and gently brush particles from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 20-30 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this MSDS and take their advice). Take care not to rinse contaminated water into the unaffected eye or onto face. If irritation persists, repeat flushing. Call a Poisons Information Centre or a doctor urgently. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting; rinse mouth thoroughly with water and contact a Poisons Information Centre. Urgent hospital treatment is likely to be needed. Give activated charcoal if instructed.

SECTION 5 - FIRE FIGHTING MEASURES

Fire and Explosion Hazards: There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. The presence of this product in a fire is likely to intensify the fire due to its oxidising properties.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Not Combustible. Use extinguishing media suited to burning materials. Coarse water spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is liquid-tight chemical protective clothing and breathing apparatus.

Flash point: Does not burn.

Upper Flammability Limit: Does not burn.

MATERIAL SAFETY DATA SHEET

Lower Flammability Limit: Does not burn.
Autoignition temperature: Not applicable - does not burn.
Flammability Class: Does not burn.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that dusts are likely to build up in cleanup area, we recommend that you use a suitable Dust Mask. Use a P1 mask, designed for use against mechanically generated particles eg silica & asbestos. Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Under no circumstances should sawdust or other combustible material be used. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Consider vacuuming if appropriate. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. Contaminated area may be neutralised by washing with weak or dilute reducing agent. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

SECTION 7 - HANDLING AND STORAGE

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area. Check containers periodically for corrosion and leaks. Containers should be kept closed in order to minimise contamination, especially from combustible or reducing materials. Make sure that the product does not come into contact with or substances listed under "Incompatibilities" in Section 10. If you keep more than 50kg of Dry Pool Chlorine, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

ASCC Exposure limits **TWA (mg/m³)** **STEL (mg/m³)**

Exposure limits have not been established by ASCC for this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that dusts are minimised.

Eye Protection: Your eyes must be completely protected from this product by splash resistant goggles with face shield. All surrounding skin areas must be covered. Emergency eye wash facilities must also be available in an area close to where this product is being used.

Skin Protection: Because of the dangerous nature of this product, make sure that all skin areas are completely covered by impermeable gloves, overalls, hair covering, apron and face shield. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC.

Respirator: If there is a significant chance that dusts are likely to build up in the area where this product is being used, we recommend that you use a suitable Dust Mask. Otherwise, not normally necessary.

MATERIAL SAFETY DATA SHEET

NSW 2204 Australia

Freecall 1800 64 POOL

Phone +61 2 9550 3900

This Revision Dated: September, 2010

Fax +61 2 9550 3536

Safety deluge showers should, if practical, be provided near to where this product is being used.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES:

Physical Description & colour:	White granular solid.
Odour:	Chlorine odour.
Boiling Point:	Not applicable.
Freezing/Melting Point:	Decomposes before melting.
Volatiles:	Nil at 100°C.
Vapour Pressure:	Negligible at normal ambient temperatures.
Vapour Density:	No data.
Specific Gravity:	2.1 approx
Water Solubility:	Soluble.
pH:	11.5 (5% in water)
Volatility:	Negligible at normal ambient temperatures.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water distribution:	No data
Autoignition temp:	Not applicable - does not burn.

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties. Check the Safety Directions on the product label for further details of incompatibilities.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep isolated from combustible materials.

Incompatibilities: reducing agents, zinc, tin, aluminium and their alloys, combustible materials, other substances reactive with oxidising agents.

Fire Decomposition: Hydrogen chloride gas, other compounds of chlorine. Calcium compounds.

Polymerisation: This product will not undergo polymerisation reactions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Calcium Hypochlorite	Conc>=25%: C; R34; R22; R31

SECTION 12 - ECOLOGICAL INFORMATION

This product is very toxic to aquatic organisms.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to separate the contamination in some way. Only if neither of these options is suitable, consider landfill, but we recommend that it be neutralised in a controlled manner before disposal.

SECTION 14 - TRANSPORT INFORMATION

ADG Code: 2880, CALCIUM HYPOCHLORITE, HYDRATED

Hazchem Code: 1W

MATERIAL SAFETY DATA SHEET

Special Provisions: 313, 314

Limited quantities: ADG 7 specifies a Limited Quantity value of 1 kg for this class of product.

Dangerous Goods Class: Class 5.1: Oxidising Agents.

Packaging Group: II

Packaging Method: P002, IBC08

Class 5.1 Oxidising Agents shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases), 2.3 (Toxic Gases), 3 (Flammable Liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.2 (Organic Peroxides), 6 (Toxic Substances, where the Toxic Substance is a fire risk substance), 7 (Radioactive Substances), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods, where the substance is a fire risk substance), Fire risk substances other than Dangerous Goods. They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-Flammable, Non-Toxic Gases), 6 (Toxic Substances except where the substances are fire risk substances), 9 (Miscellaneous Dangerous Goods except where the goods are fire risk substances) Foodstuffs and foodstuff empties.

SECTION 15 - REGULATORY INFORMATION

AICS: This product is compliant with NICNAS regulations.

The following ingredient: Calcium hypochlorite, is mentioned in the SUSDP.

SECTION 16 - OTHER INFORMATION

This MSDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
ASCC	Office of the Australian Safety and Compensation Council
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSDP	Standard for the Uniform Scheduling of Drugs & Poisons
UN Number	United Nations Number

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the ASCC document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]

Copyright © Kilford & Kilford Pty Ltd, September, 2010.

<http://www.kilford.com.au/> Phone (02)9251 4532