

Liberty 600 model Robot Cleaners

Maytronics Australia

Chemwatch: 9002-01

Version No: 3.1

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Chemwatch Hazard Alert Code: 3

Initial Date: 20/01/2026

Revision Date: 22/01/2026

Print Date: 27/01/2026

S.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

| | |
|--------------------------------------|---|
| Product name | Liberty 600 model Robot Cleaners |
| Chemical Name | Not Applicable |
| Synonyms | Not Available |
| Proper shipping name | LITHIUM ION BATTERIES (including lithium ion polymer batteries) |
| Chemical formula | Not Applicable |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| | |
|---------------------------------|--|
| Relevant identified uses | Battery. NOTE: Hazard statement relates to battery contents. Potential for exposure should not exist unless the battery leaks, is exposed to high temperatures or is mechanically, physically or electrically abused. Use involves discharge then regenerative charging cycle from external DC power source. CHARGING HAZARD. Completion of charging process includes evolution of highly flammable and explosive hydrogen gas which is readily detonated by electric spark. No smoking or naked lights. Do not attach/detach metal clips or operate open switches during charging process because of arcing/sparking hazard. Overcharging to excess results in vigorous hydrogen evolution - boiling - which may cause generation of corrosive acid mist. |
|---------------------------------|--|

Details of the manufacturer or importer of the safety data sheet

| | |
|--------------------------------|--|
| Registered company name | Maytronics Australia |
| Address | Unit 2/91 Rudd St Oxley QLD 4075 Australia |
| Telephone | 1300 693 657 |
| Fax | Not Available |
| Website | Not Available |
| Email | Not Available |

Emergency telephone number

| | |
|--|-------------------------------------|
| Association / Organisation | CHEMWATCH EMERGENCY RESPONSE (24/7) |
| Emergency telephone number(s) | +61 1800 951 288 (ID#: 9002-01) |
| Other emergency telephone number(s) | +61 3 9573 3188 |

SECTION 2 Hazards identification

Classification of the substance or mixture

| | |
|--------------------------------------|---|
| Poisons Schedule | Not Applicable |
| Classification ^[1] | Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Carcinogenicity Category 1A, Specific Target Organ Toxicity - Repeated Exposure Category 2 |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

Label elements

| | |
|---------------------|---|
| Hazard pictogram(s) |  |
|---------------------|---|

| | |
|-------------|--------|
| Signal word | Danger |
|-------------|--------|

Hazard statement(s)

| | |
|------|--|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H335 | May cause respiratory irritation. |
| H350 | May cause cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

Precautionary statement(s) Prevention

| | |
|------|--|
| P260 | Do not breathe dust/fume. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P264 | Wash all exposed external body areas thoroughly after handling. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |

Precautionary statement(s) Response

| | |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/ attention. |
| P310 | Immediately call a POISON CENTER/doctor/physician/first aider. |
| P302+P352 | IF ON SKIN: Wash with plenty of water. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |

Precautionary statement(s) Storage

| | |
|-----------|--|
| P405 | Store locked up. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

Precautionary statement(s) Disposal

| | |
|------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|--|

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|---------------|-----------|--|
| Not Available | | hermetically sealed metal case with |
| 346417-97-8 | 36-40 | <u>lithium nickel manganese cobalt oxide</u> |
| 96-49-1 | 15-20 | <u>ethylene carbonate</u> |
| 7782-42-5 | 20-26 | <u>graphite</u> |
| Not Available | 10-15 | ingredients, proprietary |
| 21324-40-3 | 1-4 | <u>lithium fluorophosphate</u> |

| CAS No | %[weight] | Name |
|---|-----------|---------------------------------|
| 24937-79-9 | 0-2 | vinylidene fluoride homopolymer |
| Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available | | |

SECTION 4 First aid measures

Description of first aid measures

| | |
|---------------------|--|
| Eye Contact | <ul style="list-style-type: none"> ▸ Generally not applicable. If this product comes in contact with eyes: <ul style="list-style-type: none"> ▸ Wash out immediately with water. ▸ If irritation continues, seek medical attention. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | <ul style="list-style-type: none"> ▸ Generally not applicable. If skin or hair contact occurs: <ul style="list-style-type: none"> ▸ Flush skin and hair with running water (and soap if available). ▸ Seek medical attention in event of irritation. |
| Inhalation | <ul style="list-style-type: none"> ▸ Generally not applicable. ▸ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▸ Other measures are usually unnecessary. |
| Ingestion | <ul style="list-style-type: none"> ▸ Generally not applicable. Not considered a normal route of entry. <ul style="list-style-type: none"> ▸ If swallowed do NOT induce vomiting. ▸ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▸ Observe the patient carefully. ▸ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▸ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▸ Seek medical advice. |

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

| | |
|-----------------------------|---|
| Fire Incompatibility | None known. <ul style="list-style-type: none"> ▸ Keep dry ▸ NOTE: May develop pressure in containers; open carefully. Vent periodically. |
|-----------------------------|---|

Advice for firefighters

| | |
|------------------------------|---|
| Fire Fighting | Slight hazard when exposed to heat, flame and oxidisers. |
| Fire/Explosion Hazard | <ul style="list-style-type: none"> ▸ Non combustible. ▸ Not considered to be a significant fire risk. ▸ Heating may cause expansion or decomposition leading to violent rupture of containers. ▸ May emit acrid smoke. May emit corrosive and poisonous fumes. Articles and manufactured articles may constitute a fire hazard where polymers form their outer layers or where combustible packaging remains in place. Certain substances, found throughout their construction, may degrade or become volatile when heated to high temperatures. This may create a secondary hazard. |
| HAZCHEM | 2Y |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Liberty 600 model Robot Cleaners

Methods and material for containment and cleaning up

| | |
|---------------------|---|
| Minor Spills | Clean up all spills immediately. Avoid contact with skin and eyes. Place in suitable containers for disposal. |
| Major Spills | <ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Wear protective clothing, safety glasses, dust mask, gloves. ▶ Secure load if safe to do so. Bundle/collect recoverable product. ▶ Use dry clean up procedures and avoid generating dust. ▶ Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). ▶ Water may be used to prevent dusting. ▶ Collect remaining material in containers with covers for disposal. ▶ Flush spill area with water. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

| | |
|--------------------------|---|
| Safe handling | Do not connect the positive terminal to the negative terminal with electrical wire or chain. Avoid polarity reverse connection when installing the battery to an instrument. Do not wet the battery with water, seawater or acid; or expose to strong oxidizer. Do not damage or remove the external tube. Keep the battery away from heat and fire. Do not disassemble or reconstruct the battery; or solder the battery directly. Do not give a mechanical shock or deform. Do not use unauthorized charger or other charging method. This battery is manufactured in a charged state. It is NOT designed for recharging. Recharging can cause battery leakage or in some cases, high pressure rupture. Inadvertent charging can occur if a battery is installed backwards. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Avoid physical damage to containers. |
| Other information | <ul style="list-style-type: none"> ▶ Keep dry. ▶ Store under cover. ▶ Protect containers against physical damage. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. <p>Keep out of reach of children. Store out of direct sunlight</p> <ul style="list-style-type: none"> ▶ Store away from incompatible materials. |

Conditions for safe storage, including any incompatibilities

| | |
|--------------------------------|--|
| Suitable container | Generally packaging as originally supplied with the article or manufactured item is sufficient to protect against physical hazards. If repackaging is required ensure the article is intact and does not show signs of wear. As far as is practicably possible, reuse the original packaging or something providing a similar level of protection to both the article and the handler. |
| Storage incompatibility | Avoid contamination of water, foodstuffs, feed or seed. <ul style="list-style-type: none"> ▶ Keep dry ▶ NOTE: May develop pressure in containers; open carefully. Vent periodically. |

SECTION 8 Exposure controls / personal protection

Control parameters


Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|------------------------------|---------------------------------------|--|---------|---------------|---------------|---|
| Australia Exposure Standards | lithium nickel manganese cobalt oxide | Manganese, dust & compounds (as Mn) | 1 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | graphite | Graphite (all forms except fibres) (respirable dust) (natural & synthetic) | 3 mg/m3 | Not Available | Not Available | (e) Containing no asbestos and < 1% crystalline silica. |

Exposure controls

| | |
|---|--|
| Appropriate engineering controls | General exhaust is adequate under normal operating conditions. Articles or manufactured items, in their original condition, generally don't require engineering controls during handling or in normal use. Exceptions may arise following extensive use and subsequent wear, during recycling or disposal operations where substances, found in the article, may be released to the environment. |
|---|--|

| | |
|--|---|
| Individual protection measures, such as personal protective equipment |  |
| Eye and face protection | None under normal operating conditions. OTHERWISE: ▶ Safety glasses. |
| Skin protection | See Hand protection below |
| Hands/feet protection | None under normal operating conditions. OTHERWISE: ▶ Rubber Gloves |
| Body protection | See Other protection below |
| Other protection | No special equipment needed when handling small quantities |

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES | A-AUS | - | A-PAPR-AUS / Class 1 |
| up to 50 x ES | - | A-AUS / Class 1 | - |
| up to 100 x ES | - | A-2 | A-PAPR-2 ^ |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Respiratory protection not normally required due to the physical form of the product.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| | | | |
|--|--|---|----------------|
| Appearance | Solid with no odour; insoluble in water. | | |
| Physical state | Manufactured | Relative density (Water = 1) | Not Available |
| Odour | No Odour | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Applicable | Decomposition temperature (°C) | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Applicable |
| Initial boiling point and boiling range (°C) | Not Applicable | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | Not Applicable | Taste | Not Available |
| Evaporation rate | Not Applicable | Explosive properties | Not Available |
| Flammability | Not Applicable | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Applicable | Surface Tension (dyn/cm or mN/m) | Not Applicable |
| Lower Explosive Limit (%) | Not Applicable | Volatile Component (%vol) | Not Applicable |
| Vapour pressure (kPa) | Not Applicable | Gas group | Not Available |
| Solubility in water | Not Available | pH as a solution (1%) | Not Applicable |
| Vapour density (Air = 1) | Not Applicable | VOC g/L | Not Applicable |
| Heat of Combustion (kJ/g) | Not Available | Ignition Distance (cm) | Not Available |
| Flame Height (cm) | Not Available | Flame Duration (s) | Not Available |
| Enclosed Space Ignition Time Equivalent (s/m³) | Not Available | Enclosed Space Ignition Deflagration Density (g/m³) | Not Available |

Continued...

SECTION 10 Stability and reactivity

| | |
|---|--|
| Reactivity | See section 7 |
| Chemical stability | <ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| | |
|---|--|
| a) Acute Toxicity | Based on available data, the classification criteria are not met. |
| b) Skin Irritation/Corrosion | There is sufficient evidence to classify this material as skin corrosive or irritating. |
| c) Serious Eye Damage/Irritation | There is sufficient evidence to classify this material as eye damaging or irritating |
| d) Respiratory or Skin sensitisation | There is sufficient evidence to classify this material as sensitising to skin or the respiratory system |
| e) Mutagenicity | Based on available data, the classification criteria are not met. |
| f) Carcinogenicity | There is sufficient evidence to classify this material as carcinogenic |
| g) Reproductivity | Based on available data, the classification criteria are not met. |
| h) STOT - Single Exposure | There is sufficient evidence to classify this material as toxic to specific organs through single exposure |
| i) STOT - Repeated Exposure | There is sufficient evidence to classify this material as toxic to specific organs through repeated exposure |
| j) Aspiration Hazard | Based on available data, the classification criteria are not met. |

| | |
|---------------------|--|
| Inhaled | Vapors or fumes may cause respiratory tract irritation. Not normally a hazard due to physical form of product. |
| Ingestion | Considered an unlikely route of entry in commercial/industrial environments Ingestion may result in nausea, abdominal irritation, pain and vomiting |
| Skin Contact | The electrolyte causes severe skin burns and irritation. Not normally a hazard due to physical form of product. |
| Eye | The electrolyte causes eye irritation and damage. Not normally a hazard due to physical form of product. |
| Chronic | The chemicals in this product are contained in a sealed case and exposure does not occur during normal handling and use. Not normally a hazard due to physical form of product. |

| Liberty 600 model Robot Cleaners | TOXICITY | IRRITATION |
|---------------------------------------|---|--|
| | Not Available | Not Available |
| lithium nickel manganese cobalt oxide | TOXICITY | IRRITATION |
| | Not Available | Not Available |
| ethylene carbonate | TOXICITY | IRRITATION |
| | dermal (rat) LD50: >2000 mg/kg ^[1] | Eye: adverse effect observed (irritating) ^[1] |
| | Oral (Rat) LD50: >2000 mg/kg ^[1] | Skin (Rodent - rabbit): 660mg - Mild Skin: no adverse effect observed (not irritating) ^[1] |
| graphite | TOXICITY | IRRITATION |
| | Inhalation (Rat) LC50: >2 mg/L4h ^[1] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50: >200 mg/kg ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| lithium fluorophosphate | TOXICITY | IRRITATION |
| | Oral (Rat) LD50: 50-300 mg/kg ^[1] | Eye: adverse effect observed (irritating) ^[1] Skin: adverse effect observed (corrosive) ^[1] |

| | | |
|---------------------------------|-----------------|-------------------|
| vinylidene fluoride homopolymer | TOXICITY | IRRITATION |
| | Not Available | Not Available |

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

| | |
|--|---|
| LITHIUM NICKEL MANGANESE COBALT OXIDE | <p>The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.</p> <p>Goitrogenic: Goitrogens are substances that suppress the function of the thyroid gland by interfering with iodine uptake, which can, as a result, cause an enlargement of the thyroid (a goitre). Goitrogens include:</p> <ul style="list-style-type: none"> - Vitexin, a flavonoid, which inhibits thyroid peroxidase, contributing to goitre - Thiocyanate and perchlorate, which decrease iodide uptake by competitive inhibition and consequently increase release of TSH from the pituitary gland - Lithium, which inhibits thyroid hormone release - Certain foods, such as soy and millet (containing vitexins) and vegetables in the genus Brassica (which includes broccoli, Brussels sprouts, cabbage, cauliflower and horseradish). - Caffeine (found in coffee, tea, cola and chocolate), which acts on thyroid function as a suppressant. |
| | <p>ETHYLENE CARBONATE</p> <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>For ethylene carbonate: Ethylene carbonate is rapidly converted to ethylene glycol, and both substances have similar toxicity in animals. In animals, chronic exposure has resulted in kidney damage. Testing has not shown ethylene carbonate to cause genetic toxicity. At sufficient doses, ethylene carbonate caused birth defects.</p> <p>For ethylene glycol:</p> <p>Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited information suggests that it is also absorbed through the airways; absorption through skin is apparently slow. Following absorption, it is distributed throughout the body. In humans, it is initially metabolized by alcohol dehydrogenase to form glycoaldehyde, which is rapidly converted to glycolic acid and glyoxal. These breakdown products are oxidized to glyoxylate, which may be further metabolized to formic acid, oxalic acid, and glycine. Breakdown of both glycine and formic acid can generate carbon dioxide, which is one of the major elimination products of ethylene glycol. In addition to exhaled carbon dioxide, ethylene glycol is eliminated in the urine as both the parent compound and glycolic acid. Elimination is rapid and occurs within a few hours.</p> <p>Respiratory effects: Respiratory system involvement occurs 12-24 hours after swallowing sufficient amounts of ethylene glycol. Symptoms include hyperventilation, shallow rapid breathing, and generalized swelling of the lungs with calcium oxalate deposits occasionally appearing in the lungs. Respiratory system involvement appears to be dose-dependent and occurs at the same time as cardiovascular changes. Later, there may be other changes compatible with adult respiratory distress syndrome (ARDS). Swelling of the lung can be a result of heart failure, ARDS, or aspiration of stomach contents. Symptoms related to acidosis such as fast or excessive breathing are frequently observed; however, major symptoms such as swelling of the lung and inflammation of the bronchi and lungs are relatively rare, and are usually seen only in extreme poisoning.</p> <p>Cardiovascular effects: Cardiovascular system involvement in humans occurs at the same time as respiratory system involvement, during the second phase of ethylene glycol poisoning by swallowing, which is 12-24 hours after acute exposure. The symptoms of poisoning involving the heart include increased heart rate, heart enlargement and ventricular gallop. There may also be high or low blood pressure, which may progress to cardiogenic shock. In lethal cases, inflammation of the heart muscle has been observed at autopsy. Cardiovascular involvement appears to be rare and usually seen after swallowing higher doses of ethylene glycol. In summary, acute exposure to high levels of ethylene glycol can cause serious cardiovascular effects in humans. The effects of a long-term, low-dose exposure are unknown.</p> <p>Gastrointestinal effects: Common early acute effects of swallowing ethylene glycol include nausea, vomiting with or without blood, heartburn and abdominal cramping and pain. One patient showed intermittent diarrhea and pain, and after surgery, deposition of oxalate crystals was shown to have occurred.</p> <p>Musculoskeletal effects: Reported musculoskeletal effects in cases of acute ethylene glycol poisoning include diffuse muscle tenderness and pain, associated with high levels of creatinine in the blood, and jerks and contractions associated with low calcium.</p> <p>Liver effects: Autopsies carried out on people who died following acute ethylene glycol poisoning showed deposition of calcium oxalate in the liver as well as hydropic and fatty degeneration and cell death (necrosis) of the liver.</p> <p>Kidney effects: Adverse kidney effects are seen during the third stage of ethylene glycol poisoning, 2-3 days after acute exposure. Calcium oxalate crystals are deposited in the tubules and are seen in the urine. There may also be degeneration and death of tubule cells, and inflammation of the tubule interstitium. If untreated, the degree of kidney damage progresses and leads to blood and protein in the urine, decreased kidney function, reduction in urine output and ultimately, kidney failure. With adequate supportive therapy, kidney function can return to normal or near normal.</p> <p>Metabolic effects: Metabolic changes can occur within 12 hours of exposure to ethylene glycol. There may be metabolic acidosis, caused by accumulation of glycolic acid in the blood and therefore a reduction in blood pH. The anion gap is increased, due to increased unmeasured anions (mainly glycolate).</p> <p>Effects on the nervous system: Adverse reactions involving the nervous system are among the first symptoms to appear in humans after ethylene glycol is swallowed. These early effects are also the only symptoms caused by unmetabolised ethylene glycol. Together with metabolic effects (see above), they occur from 0.5-12 hours after exposure and are considered to be part of the first stage in ethylene glycol poisoning. Inco-ordination, slurred speech, confusion and sleepiness are common in the early</p> |

Liberty 600 model Robot Cleaners

| | |
|---|---|
| | <p>stages, as are irritation, restlessness and disorientation. Later, there may be effects on cranial nerves (which may be reversible over many months). Swelling of the brain (cerebrum) and crystal deposits of calcium oxalate in the walls of the small blood vessels of the brain were found at autopsy in people who died after acute ethylene glycol poisoning.</p> <p>Reproductive effects: Animal testing showed that ethylene glycol may affect fertility, survival of fetuses and the male reproductive organs.</p> <p>Effects on development: Animal studies indicate that birth defects may occur after exposure in pregnancy; there may also be reduction in foetal weight.</p> <p>Cancer: No studies are known regarding cancer effects in humans or animal, after skin exposure to ethylene glycol.</p> <p>Genetic toxicity: No human studies available, but animal testing results are consistently negative.</p> |
| LITHIUM NICKEL MANGANESE COBALT OXIDE & GRAPHITE & LITHIUM FLUOROPHOSPHATE & VINYLIDENE FLUORIDE HOMOPOLYMER | No significant acute toxicological data identified in literature search. |
| ETHYLENE CARBONATE & GRAPHITE & LITHIUM FLUOROPHOSPHATE | Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. |

| | | | |
|--|---|---------------------------------|---|
| Acute Toxicity | ✗ | Carcinogenicity | ✓ |
| Skin Irritation/Corrosion | ✓ | Reproductivity | ✗ |
| Serious Eye Damage/Irritation | ✓ | STOT - Single Exposure | ✓ |
| Respiratory or Skin sensitisation | ✓ | STOT - Repeated Exposure | ✓ |
| Mutagenicity | ✗ | Aspiration Hazard | ✗ |

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

| | Endpoint | Test Duration (hr) | Species | Value | Source |
|--|---------------|--------------------|-------------------------------|---------------|---------------|
| Liberty 600 model Robot Cleaners | Not Available | Not Available | Not Available | Not Available | Not Available |
| lithium nickel manganese cobalt oxide | Not Available | Not Available | Not Available | Not Available | Not Available |
| ethylene carbonate | EC50 | 72h | Algae or other aquatic plants | >100mg/l | 2 |
| | EC50 | 48h | Crustacea | >100mg/l | 2 |
| | LC50 | 96h | Fish | >100mg/l | 2 |
| | NOEC(ECx) | 72h | Algae or other aquatic plants | 100mg/l | 2 |
| graphite | EC50 | 72h | Algae or other aquatic plants | >100mg/l | 2 |
| | EC50 | 48h | Crustacea | >100mg/l | 2 |
| | NOEC(ECx) | 96h | Fish | >=100mg/l | 2 |
| | LC50 | 96h | Fish | >100mg/l | 2 |

| lithium fluorophosphate | Endpoint | Test Duration (hr) | Species | Value | Source |
|---------------------------------|---------------|--------------------|-------------------------------|---------------|---------------|
| | NOEC(ECx) | 528h | Fish | 0.2mg/l | 2 |
| | EC50 | 72h | Algae or other aquatic plants | 62mg/l | 2 |
| | EC50 | 48h | Crustacea | 98mg/l | 2 |
| | EC50 | 96h | Algae or other aquatic plants | 43mg/l | 2 |
| | LC50 | 96h | Fish | 42mg/l | 2 |
| vinylidene fluoride homopolymer | Endpoint | Test Duration (hr) | Species | Value | Source |
| | Not Available | Not Available | Not Available | Not Available | Not Available |

Legend: *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data*

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|---------------------------------|-------------------------|------------------|
| ethylene carbonate | HIGH | HIGH |
| vinylidene fluoride homopolymer | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|---------------------------------|------------------------|
| ethylene carbonate | LOW (LogKOW = -0.3388) |
| vinylidene fluoride homopolymer | LOW (LogKOW = 1.24) |

Mobility in soil

| Ingredient | Mobility |
|---------------------------------|-----------------------|
| ethylene carbonate | LOW (Log KOC = 9.168) |
| vinylidene fluoride homopolymer | LOW (Log KOC = 35.04) |


SECTION 13 Disposal considerations

Waste treatment methods

| Product / Packaging disposal | |
|------------------------------|---|
| | <ul style="list-style-type: none"> ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Management Authority for disposal. |

SECTION 14 Transport information

Labels Required

| | |
|------------------|---|
| |  |
| Marine Pollutant | NO |
| HAZCHEM | 2Y |

Land transport (ADG)

| | |
|----------------------------------|---|
| 14.1. UN number or ID number | 3480 |
| 14.2. UN proper shipping name | LITHIUM ION BATTERIES (including lithium ion polymer batteries) |
| 14.3. Transport hazard class(es) | Class 9 |

Continued...

Liberty 600 model Robot Cleaners

| | | |
|------------------------------------|--------------------|---------------------------------|
| | Subsidiary Hazard | Not Applicable |
| 14.4. Packing group | Not Applicable | |
| 14.5. Environmental hazard | Not Applicable | |
| 14.6. Special precautions for user | Special provisions | 188 230 310 348 376 377 384 387 |
| | Limited quantity | 0 |

Air transport (ICAO-IATA / DGR)

| | | |
|------------------------------------|---|---|
| 14.1. UN number | 3480 | |
| 14.2. UN proper shipping name | Lithium ion batteries (including lithium ion polymer batteries) | |
| 14.3. Transport hazard class(es) | ICAO/IATA Class | 9 |
| | ICAO / IATA Subsidiary Hazard | Not Applicable |
| | ERG Code | 12FZ |
| 14.4. Packing group | Not Applicable | |
| 14.5. Environmental hazard | Not Applicable | |
| 14.6. Special precautions for user | Special provisions | A88 A99 A154 A164 A183 A201 A213 A331 A334 A802 |
| | Cargo Only Packing Instructions | See 965 |
| | Cargo Only Maximum Qty / Pack | See 965 |
| | Passenger and Cargo Packing Instructions | Forbidden |
| | Passenger and Cargo Maximum Qty / Pack | Forbidden |
| | Passenger and Cargo Limited Quantity Packing Instructions | Forbidden |
| | Passenger and Cargo Limited Maximum Qty / Pack | Forbidden |

Sea transport (IMDG-Code / GGVSee)

| | | |
|------------------------------------|---|---------------------------------|
| 14.1. UN number | 3480 | |
| 14.2. UN proper shipping name | LITHIUM ION BATTERIES (including lithium ion polymer batteries) | |
| 14.3. Transport hazard class(es) | IMDG Class | 9 |
| | IMDG Subsidiary Hazard | Not Applicable |
| 14.4. Packing group | Not Applicable | |
| 14.5. Environmental hazard | Not Applicable | |
| 14.6. Special precautions for user | EMS Number | F-A, S-I |
| | Special provisions | 188 230 310 348 376 377 384 387 |
| | Limited Quantities | 0 |

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|---------------------------------------|----------------|
| lithium nickel manganese cobalt oxide | Not Applicable |
| ethylene carbonate | Not Applicable |
| graphite | Not Applicable |
| lithium fluorophosphate | Not Applicable |
| vinylidene fluoride homopolymer | Not Applicable |

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|---------------------------------------|----------------|
| lithium nickel manganese cobalt oxide | Not Applicable |
| ethylene carbonate | Not Applicable |
| graphite | Not Applicable |
| lithium fluorophosphate | Not Applicable |
| vinylidene fluoride homopolymer | Not Applicable |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

lithium nickel manganese cobalt oxide is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

ethylene carbonate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

graphite is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

lithium fluorophosphate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

vinylidene fluoride homopolymer is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

Additional Regulatory Information

Not Applicable

National Inventory Status

| National Inventory | Status |
|---|--|
| Australia - AIIC / Australia Non-Industrial Use | No (lithium nickel manganese cobalt oxide) |
| Canada - DSL | No (lithium nickel manganese cobalt oxide; lithium fluorophosphate) |
| Canada - NDCL | No (lithium nickel manganese cobalt oxide; ethylene carbonate; graphite; vinylidene fluoride homopolymer) |
| China - IECSC | No (lithium nickel manganese cobalt oxide) |
| Europe - EINEC / ELINCS / NLP | No (lithium nickel manganese cobalt oxide; vinylidene fluoride homopolymer) |
| Japan - ENCS | No (lithium nickel manganese cobalt oxide; graphite) |
| Korea - KECI | No (lithium nickel manganese cobalt oxide) |
| New Zealand - NZIoC | No (lithium nickel manganese cobalt oxide; lithium fluorophosphate) |
| Philippines - PICCS | No (lithium nickel manganese cobalt oxide) |
| USA - TSCA | TSCA Inventory 'Active' substance(s) (ethylene carbonate; graphite; lithium fluorophosphate; vinylidene fluoride homopolymer); No (lithium nickel manganese cobalt oxide) |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | No (lithium nickel manganese cobalt oxide; ethylene carbonate; lithium fluorophosphate; vinylidene fluoride homopolymer) |
| Vietnam - NCI | Yes |
| Russia - FBEPH | No (lithium nickel manganese cobalt oxide; lithium fluorophosphate) |
| UAE - Control List (Banned/Restricted Substances) | No (lithium nickel manganese cobalt oxide; ethylene carbonate; lithium fluorophosphate; vinylidene fluoride homopolymer) |
| Legend: | Yes = All CAS declared ingredients are on the inventory |

Continued...

| National Inventory | Status |
|--------------------|--|
| | No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

| | |
|---------------|------------|
| Revision Date | 22/01/2026 |
| Initial Date | 20/01/2026 |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|----------------|--|
| 3.1 | 22/01/2026 | Physical and chemical properties - Appearance, Identification of the substance / mixture and of the company / undertaking - Supplier Information |

Other information

Ingredients with multiple cas numbers

| Name | CAS No |
|----------|---|
| graphite | 7782-42-5, 115344-49-5, 1215114-94-5, 12424-49-6, 12751-41-6, 1397692-45-3, 1399-57-1, 155660-93-8, 156854-02-3, 159251-18-0, 164973-65-3, 1811526-35-8, 182761-22-4, 2093098-71-4, 2179292-22-7, 2183464-49-3, 37265-44-4, 37265-48-8, 50814-81-8, 72840-52-9, 82696-74-0, 82696-75-1, 82701-02-8, 82701-03-9, 82701-04-0, 82701-05-1, 82701-06-2, 82709-42-0, 83797-07-3, 84739-05-9, 857167-12-5, 87934-03-0 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- ▶ PC - TWA: Permissible Concentration-Time Weighted Average
- ▶ PC - STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit,
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- ▶ IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code

- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European Inventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECl: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas

- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.