

Clark Rubber

Chemwatch: 5630-98 Version No: 2.1

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Issue Date: **06/10/2023** Print Date: **05/02/2025**

S.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	070 FILTRITE EXTREME ALGAECIDE
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains copper sulfate and benzyl C12-14 alkyldimethylammonium chloride)
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Swimming pool algaecide and clarifier for black spot & other algae, Use in conjunction with chlorination. Dose 1L/50000L.
	Use according to manufacturer's directions.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Clark Rubber		
Address	National Support Office, 1/12 Elizabeth Street, Hawthorn VIC 3122 Australia		
Telephone	+61 3 8727 9914		
Fax	+61 3 9729 3266		
Website	https://www.clarkrubber.com.au		
Email	reception@clarkrubber.com.au		

Emergency telephone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE (24/7)	
Emergency telephone number(s)	+61 1800 951 288	
Other emergency telephone number(s)	+61 3 9573 3188	

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	S5
Classification ^[1]	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Carcinogenicity Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI



Signal word Danger

Hazard statement(s)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313	IF exposed or concerned: Get medical advice/ attention.		
P310	Immediately call a POISON CENTER/doctor/physician/first aider.		
P302+P352	IF ON SKIN: Wash with plenty of water.		
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.		
P362+P364	Take off contaminated clothing and wash it before reuse.		
P391	Collect spillage.		
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.		
P304+P340	40 IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P330	Rinse mouth.		

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7758-98-7	1-10	copper sulfate
85409-22-9	1-10	benzyl C12-14 alkyldimethylammonium chloride
141-43-5	1-10	ethanolamine

CAS No	%[weight]	Name
102-71-6	1-10	triethanolamine
Not Available	balance	Ingredients determined not to be hazardous
Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 Annex VI: 4. Classification drawn from C&L: * EU IOELVs available		

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

for copper intoxication:

- Unless extensive vomiting has occurred empty the stomach by lavage with water, milk, sodium bicarbonate solution or a 0.1% solution of potassium ferrocyanide (the resulting copper ferrocyanide is insoluble).
- Administer egg white and other demulcents.
- Maintain electrolyte and fluid balances.
- Morphine or meperidine (Demerol) may be necessary for control of pain.
- If symptoms persist or intensify (especially circulatory collapse or cerebral disturbances, try BAL intramuscularly or penicillamine in accordance with the supplier's recommendations.
- Treat shock vigorously with blood transfusions and perhaps vasopressor amines.
- If intravascular haemolysis becomes evident protect the kidneys by maintaining a diuresis with mannitol and perhaps by alkalinising the urine with sodium bicarbonate.
- It is unlikely that methylene blue would be effective against the occassional methaemoglobinemia and it might exacerbate the subsequent haemolytic episode.
- Institute measures for impending renal and hepatic failure.

[GOSSELIN, SMITH & HODGE: Commercial Toxicology of Commercial Products]

- A role for activated charcoals for emesis is, as yet, unproven.
- In severe poisoning CaNa2EDTA has been proposed.

[ELLENHORN & BARCELOUX: Medical Toxicology]

For acute or short-term repeated exposures to highly alkaline materials:

- Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- Oxygen is given as indicated.
- The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

- Milk and water are the preferred diluents
- No more than 2 glasses of water should be given to an adult.
- Neutralising agents should never be given since exothermic heat reaction may compound injury.
- * Catharsis and emesis are absolutely contra-indicated.

* Activated charcoal does not absorb alkali.

* Gastric lavage should not be used.

- Supportive care involves the following:
- Withhold oral feedings initially.
- If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

For exposures to quaternary ammonium compounds;

- For ingestion of concentrated solutions (10% or higher): Swallow promptly a large quantity of milk, egg whites / gelatin solution. If not readily available, a slurry of activated charcoal may be useful. Avoid alcohol. Because of probable mucosal damage omit gastric lavage and emetic drugs.
- For dilute solutions (2% or less): If little or no emesis appears spontaneously, administer syrup of Ipecac or perform gastric lavage.
- If hypotension becomes severe, institute measures against circulatory shock.
- If respiration laboured, administer oxygen and support breathing mechanically. Oropharyngeal airway may be inserted in absence of gag reflex. Epiglottic or laryngeal edema may necessitate a tracheotomy.
- Persistent convulsions may be controlled by cautious intravenous injection of diazepam or short-acting barbiturate drugs. [Gosselin et al, Clinical Toxicology of Commercial Products]

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	---

Advice for firefighters

Fire Fighting Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. Combustion products include: carbon dioxide (CO2) nitrogen oxides (NOx) metal oxides other pyrolysis products typical of burning organic material. HAZCHEM AZ Hazchelm Azeita deliver of burning organic material. Hazchelm Sight for the sard of burning organic material. Maxie containing combustion for the pyrolysis products typical of burning organic material. Hazchelm Hazchelm Hazchelm Hazchelm Hazchelm Hazchelm Hazchelm Heating and the sard deliver of t		
Fire/Explosion Hazard• Combustible.Fire/Explosion Hazard• Slight fire hazard when exposed to heat or flame.• Heating may cause expansion or decomposition leading to violent rupture of containers.• On combustion, may emit toxic fumes of carbon monoxide (CO).• May emit acrid smoke.• Mists containing combustible materials may be explosive.• Combustion products include: carbon dioxide (CO2) nitrogen oxides (NOx) metal oxides other pyrolysis products typical of burning organic material.HAZCHEM•3Z	Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
HAZCHEM •3Z	Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. Combustion products include: carbon dioxide (CO2) nitrogen oxides (NOx) metal oxides other pyrolysis products typical of burning organic material.
	HAZCHEM	•3Z

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

- Environmental hazard contain spillage.Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

	 Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Environmental hazard - contain spillage. Moderate hazard. • Clear area of personnel and move upwind. • Alert Fire Brigade and tell them location and nature of hazard. • Wear breathing apparatus plus protective gloves. • Prevent, by any means available, spillage from entering drains or water course. • No smoking, naked lights or ignition sources. • No smoking, naked lights or ignition sources. • Increase ventilation. • Stop leak if safe to do so. • Contain spill with sand, earth or vermiculite. • Collect recoverable product into labelled containers for recycling. • Absorb remaining product with sand, earth or vermiculite. • Collect solid residues and seal in labelled drums for disposal. • Wash area and prevent runoff into drains. • If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

	Alkanolamines and iron may produced unstable complexes. Monoethanolamine (MEA) and iron form a trisethanolamino-iron
	complex. This material may produce a distance complexes, monocularional and the full of the normal material may enough an an and the suspected of the suspected
	complex. This matching applications are the second at a matching the second and the second at the se
	used low pressure steam in stainless steal coils should be considered. Drum beating should also be reviewed and where
	used, tow pressure steart in statiness steer outs should be considered. Drain nearing should also be reviewed and, where
	b DO NOT allow detbing wet with material to stay in sented with skin
	Do Not anow counting wet with indefinition to stay in contact with SKin
	 Avoid all personal contact, including initiatation.
	 Weat protective clothing when hisk of exposure occurs.
	• Ose in a weil-veniliated area.
	 Prevent concentration in nollows and sumps.
Safe handling	• DO NOT enter contined spaces until atmosphere has been checked.
	 Avoid smoking, naked lights or ignition sources.
	 Avoid contact with incompatible materials.
	When handling, DO NOT eat, drink or smoke.
	Keep containers securely sealed when not in use.
	Avoid physical damage to containers.
	Always wash hands with soap and water after handling.
	Work clothes should be laundered separately.
	Use good occupational work practice.
	 Observe manufacturer's storage and handling recommendations contained within this SDS.
	Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
	 Store in original containers.
	Keep containers securely sealed.
	No smoking, naked lights or ignition sources.
Other information	Store in a cool, dry, well-ventilated area.
	Store away from incompatible materials and foodstuff containers.
	Protect containers against physical damage and check regularly for leaks.
	Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	 Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. Avoid strong bases. Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes	
Australia Exposure Standards	ethanolamine	Ethanolamine	3 ppm / 7.5 mg/m3	15 mg/m3 / 6 ppm	Not Available	Not Available	
Australia Exposure Standards	triethanolamine	Triethanolamine	5 mg/m3	Not Available	Not Available	Not Available	
Ingredient	Original IDLH			Revised IDLH			
copper sulfate	Not Available	Not Available			Not Available		
benzyl C12-14 alkyldimethylammonium chloride	Not Available		Not Available				
ethanolamine	30 ppm		Not Available				
triethanolamine	Not Available			Not Available			

Exposure controls

	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the					
	Type of Contaminant:		Air Speed:			
	solvent, vapours, degreasing etc., evaporating from tank (i	0.25-0.5 m/s (50- 100 f/min.)				
Appropriate engineering controls	aerosols, fumes from pouring operations, intermittent conta welding, spray drift, plating acid fumes, pickling (released a	0.5-1 m/s (100- 200 f/min.)				
	direct spray, spray painting in shallow booths, drum filling, discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200- 500 f/min.)				
	grinding, abrasive blasting, tumbling, high speed wheel ge into zone of very high rapid air motion).	2.5-10 m/s (500- 2000 f/min.)				
	Within each range the appropriate value depends on:					
	Lower end of the range	Upper end of the range				
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents				
	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity				
	3: Intermittent, low production.	3: High production, heavy use				
	4: Large hood or large air mass in motion	4: Small hood-local control only				
	Simple theory shows that air velocity falls rapidly with distance generally decreases with the square of distance from the ext extraction point should be adjusted, accordingly, after referent extraction fan, for example, should be a minimum of 1-2 m/s meters distant from the extraction point. Other mechanical or apparatus, make it essential that theoretical air velocities are	ce away from the opening of a simple extractior raction point (in simple cases). Therefore the a nee to distance from the contaminating source. (200-400 f/min) for extraction of solvents gene onsiderations, producing performance deficits v e multiplied by factors of 10 or more when extra	n pipe. Velocity ir speed at the The air velocity at the rated in a tank 2 vithin the extraction ction systems are			

Individual protection measures, such as personal protective equipment installed or used.

Eye and face protection

- Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.
- Chemical goggles. Whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. [AS/NZS 1337.1, EN166 or national equivalent]

	 Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection. Alternatively a gas mask may replace splash goggles and face shields. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].
Skin protection	See Hand protection below
Hands/feet protection	 Elbow length PVC gloves NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as stoes, bells and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: I equency and duration of contact, othernical resistance of glove material, glove thickness and Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 on higher (breakthrough time greater than 200 minutes according to EN 374, AS/NZS 2161.1.0 to rational equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contaminated gloves should be replaced. So defined in ASTM F-739-96 in any application, gloves are rated as: Excellent when breakthrough time > 20 min Fair when breakthrough time
Body protection	See Other protection below
Other protection	 Overalls. P.V.C apron. Barrier cream. Skin cleansing cream. Eye wash unit.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

070 FILTRITE EXTREME ALGAECIDE

Material	CPI
BUTYL	А
NATURAL+NEOPRENE	А
NEOPRENE	A

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum	Half-Face	Full-Face	Powered Air
Protection Factor	Respirator	Respirator	Respirator
up to 10 x ES	AK-AUS P2	-	AK-PAPR-AUS / Class 1 P2

NEOPRENE/NATURAL	А
NITRILE	А
PVA	А
NATURAL RUBBER	В
PVC	В
BUTYL/NEOPRENE	С
HYPALON	С
NITRILE+PVC	С
VITON	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

 $\ensuremath{\textbf{NOTE}}$: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Ansell Glove Selection

Glove — In order of recommendation
AlphaTec® Solvex® 37-185
AlphaTec® 58-008
AlphaTec® 15-554
AlphaTec® 38-612
AlphaTec® 58-530B
AlphaTec® 58-530W
AlphaTec® 58-735
AlphaTec® Solvex® 37-675
AlphaTec 02-100
AlphaTec® 79-700

The suggested gloves for use should be confirmed with the glove supplier.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear blue liquid with characteristic odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	1.05-1.1
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	7-8	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available

up to 50 x ES	-	AK-AUS / Class 1 P2	-
up to 100 x ES	-	AK-2 P2	AK-PAPR-2 P2 ^
^ - Full-face			

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 deqC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

76ak-p()

Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

There is sufficient evidence to classify this material as acutely toxic. There is sufficient evidence to classify this material as skin corrosive or irritating. There is sufficient evidence to classify this material as eye damaging or irritating There is sufficient evidence to classify this material as eye damaging or irritating There is sufficient evidence to classify this material as sensitising to skin or the respiratory system Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as carcinogenic Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and asturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
There is sufficient evidence to classify this material as skin corrosive or irritating. There is sufficient evidence to classify this material as eye damaging or irritating There is sufficient evidence to classify this material as sensitising to skin or the respiratory system Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as carcinogenic Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as carcinogenic Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and saturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
There is sufficient evidence to classify this material as eye damaging or irritating There is sufficient evidence to classify this material as sensitising to skin or the respiratory system Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as carcinogenic Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and saturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
There is sufficient evidence to classify this material as sensitising to skin or the respiratory system Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as carcinogenic Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and saturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as carcinogenic Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and saturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
There is sufficient evidence to classify this material as carcinogenic Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and saturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Based on available data, the classification criteria are not met. There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and saturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
There is sufficient evidence to classify this material as toxic to specific organs through single exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and saturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and saturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Based on available data, the classification criteria are not met. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and saturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Rats exposed to triethanolamine for six hours showed no abnormality. Monoethanolamine vapours, mists and liquid are corrosive to the mouth and throat. When rats were exposed to a highly enriched and saturated atmosphere at ambient temperatures, no fatalities were recorded. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
A metallic taste, nausea, vomiting and burning feeling in the upper stomach region occur after ingestion of copper and its derivatives. The vomitus is usually green/blue and discolours contaminated skin. Ingestion of triethanolamine may cause gastro-intestinal irritation with bleeding, burning or painful sensations in the mouth, throat, chest and abdomen, vomiting and diarrhoea. Animal testing has also shown sluggishness, excessive tear secretion, hairs standing up, unsteady gait, and red/brown discharge on hair around the nose and genitals. Lethal dose in 70 kg man is 560gms. Ethanolamine is an intermediate metabolites of certain animal producing phospholipids and choline. In poisoned rats, monoethanolamine may cause excessive tear secretion, hair erection, defective vertebral curvature, unsteady gait, weight loss, discharge around the eye, anus and genitalia.
This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Exposure to copper, by skin, has come from its use in pigments, ointments, ornaments, jewellery, dental amalgams and IUDs (intra-uterine devices), and in killing fungi and algae. Although copper is used in the treatment of water in swimming pools and reservoirs, there are no reports of toxicity from these applications. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin exposure to triethanolamine may cause slight irritation with itching, local redness, swelling and tissue destruction, sensitisation (in a small proportion of individuals), and reddened blisters. Exposure of animals to toxic levels of triethanolamine may cause sluggishness, unsteady gait, emaciation and discolouration of body organs.

	Oral and skin exposure to ethanolamine may produce weakness respiratory tract, intestines, thymus, kidneys and the skin (ulcera due to a high absorption rate. Skin contact with the material may damage the health of the indi	, abdominal distension, emaciation and damage to the tion and burn like effect). These are worse with skin exposure <i>v</i> idual; systemic effects may result following absorption.	
Eye	If applied to the eyes, this material causes severe eye damage. Copper salts, in contact with the eye, may produce inflammation of the conjunctiva, or even ulceration and cloudiness of the cornea. A drop of ethanolamine into eye causes injury slightly less than that produced by ammonia say grade 9, on a 1 to10 scale, but that into the rabbit eyes (0.005 ml) caused severe eye injury with vascularisation, deformation, severe iris inflammation and conjunctival irritation.		
Chronic	Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Prolonged or chronic exposure to alkanolamines may result in liver, kidney or nervous system injury. Repeated inhalation may aggravate asthma and lung disease involving inflammation or scarring. Results of animal testing with diethanolamine (DEA) and monoethanolamine (MEA) has shown a wide range of possible effects, including induction of tumours, developmental abnormalities and injury to the foetus and mother. Many amines greatly sensitise the skin and respiratory system, and certain individuals, especially those predisposed to asthma and other allergic responses, may show allergic reactions when chronically exposed to alkanolamines. For copper and its compounds (typically copper chloride): Acute toxicity: There are no reliable acute oral toxicity results available. Animal testing shows that skin in exposure to copper may lead to hardness of the skin, scar formation, exudation and reddish changes. Inflammation, irritation and injury of the skin were noted. Repeat dose toxicity: Animal testing shows that very high levels of copper monochloride may cause anaemia. Genetic toxicity: Copper monochloride does not appear to cause mutations in vivo, although chromosomal aberrations were see at very high concentrations in vitro. Cancer-causing potential: There was insufficient information to evaluate the cancer-causing activity of copper monochloride. Prolonged or repeated skin contact may cause degreasing, followed by drying, cracking and skin inflammation. Triethanolamine is reported to cause reversible kidney and liver damage but not cancer or foetal toxicity. However, its reaction with nitrites and nitrous acid may p		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
ALGAECIDE	Oral (None) LD50: 1185 mg/kg* ^[2]	Not Available	

	τοχιςιτγ	IRRITATION
copper sulfate	dermal (rat) LD50: >2000 mg/kg ^[1]	Skin (Human - woman): 2%
	Oral (Rat) LD50: 300 mg/kg ^[2]	
	τοχιζιτγ	IRRITATION
benzyl C12-14	Dermal (rabbit) LD50: 2730 mg/kg ^[1]	Not Available
alkyldimethylammonium chloride	Inhalation (Rat) LC50: 0.22 mg/l4h ^[1]	
	Oral (Rat) LD50: ~358 mg/kg ^[1]	
	ΤΟΧΙΟΙΤΥ	IRRITATION
	Dermal (rabbit) LD50: 1000 mg/kg ^[2]	Eye (Rodent - rabbit): 250ug - Severe
other elemine	Inhalation(Guinea) LC50; ~0.145 mg/l4h ^[2]	Eye: adverse effect observed (irreversible damage) ^[1]
ethanolamine	Oral (Guinea) LD50; 620 mg/kg ^[2]	Skin (Mammal - species unspecified): 5%
		Skin (Rodent - rabbit): 505mg - Moderate
		Skin: adverse effect observed (corrosive) ^[1]
triethanolamine	ΤΟΧΙΟΙΤΥ	IRRITATION
	dermal (rat) LD50: >16000 mg/kg ^[2]	Eye (Rodent - rabbit): 10mg - Mild
	Oral (Rabbit) LD50; 2200 mg/kg ^[2]	Eye (Rodent - rabbit): 20mg - Severe
		Eye: no adverse effect observed (not irritating) ^[1]
		Skin (Human): 15mg/3D (intermittent) - Mild
		Skin (Rodent - mouse): 50% - Severe

		Skin (Rodent - rabbit): 560mg/24H - Mild		
		Skin: no adverse effect observed (not irritating) $^{\left[1\right] }$		
Legend:	1. Value obtained from Europe ECHA Registered Substances - Unless otherwise specified data extracted from RTECS - Regis	Acute toxicity 2. Value obtained from manufacturer's SDS. ster of Toxic Effect of chemical Substances		
COPPER SULFATE	For copper sulfate Copper sulfate is corrosive. Side effects are diverse and multi signs, metallic taste in the mouth, burning pain in the chest, h kidneys. It has been reported as a cause of human suicide. O and eye, also, eczema and allergic reactions. Long term effect likely in individuals with Wilson's disease, a condition which o adverse effects on reproduction and fertility as well as canced there is residual accumulation the liver, brain, heart, kidney a	ti-systemic, and include severe gastrointestinal symptoms and neadache, sweating, shock and damage to brain, liver and On exposure, it can cause dose dependent damage to the skin cts can lead to anaemia and degenerative changes and are mo causes excessive absorption and storage of copper. It has r and embryo toxic effects. Although it is excreted in the faeces, and muscles.		
BENZYL C12-14 LKYLDIMETHYLAMMONIUM CHLORIDE	For similar compound benzyl C12-18 alkyldimethyl ammonium chloride CAS RN 68391-01-5: For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airway from direct exposure to inhaled acidic mists (which also protects the stomach lining from the hydrochloric acid secreted there). The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration. Alkyldimethylbenzylammonium chlorides are in the list of dangerous substances of council directive, classified as "harmful in contact with skin and on ingestion", and "corrosive and very toxic to aquatic organisms". It can cause dose dependent skin and eye irritation with possible deterioration of vision, possible sensitisation in those with pre-existing eczema. It does not cause cancer, genetic defect, foetal or developmental abnormality.			
ETHANOLAMINE	* Bayer			
TRIETHANOLAMINE	in thymus weight, changes in liver weight, dermatitis after syst Equivocal tumourigen by RTECS criteria. Dermal rabbit value Union Carbide The following information refers to contact allergens as a gro Contact allergies quickly manifest themselves as contact ecz pathogenesis of contact eczema involves a cell-mediated (T skin reactions, e.g. contact urticaria, involve antibody-mediatt not simply determined by its sensitisation potential: the distrit are equally important. A weakly sensitising substance which i with stronger sensitising potential with which few individuals of noteworthy if they produce an allergic test reaction in more th Studies done show that triethanolamine is of low toxicity follo inhalation. It has not been shown to cause cancer, genetic de A Cosmetic Ingredient Review (CIR) expert panel conducted The panel was concerned with the levels of free diethanolam ingredients. The panel stated that the amount of free diethan and concentration of diethanolamine. The Panel concluded that TEA and 31 related TEA-containing when the levels of free diethanolamine do not exceed the pre products in which N-nitroso compounds can be formed. Dermal carcinogenicity studies performed by the NTP on TE/ mice based on the occurrence of liver hemangiosarcoma, so increased incidences of hepatocellular adenoma, and equivo marginal increase in the incidence of renal tubule cell adenor in mice via a choline-depletion mode of action. Humans are r are considered to have little relevance to humans regarding t The panel was concerned that the potential exists for dermal related ingredients. The panel specified that products contair Tertiary alkyl amines such as TEA do not react with N-nitrosa amines can act as precursors in nitrosamine formation by un- diethanolamine) can then be N-nitrosated to products that ma occur, TEA and TEA-containing ingredients should not be use formed. Safety Assessment of Triethanolamine and Triethanolamine- Journal of Toxicology (supplement 1) 59S-83S. 2013 https://citeseerx.ist.psu.edu/viewdoc/	stemic exposure, kidney, ureter, bladder tumours recorded. e quoted above is for occluded patch in male or female animals i up and may not be specific to this product. tema, more rarely as urticaria or Quincke's oedema. The lymphocytes) immune reaction of the delayed type. Other allergin ed immune reactions. The significance of the contact allergen is poution of the substance and the opportunities for contact with it is widely distributed can be a more important allergen than one come into contact. From a clinical point of view, substances are nan 1% of the persons tested. wing high dose exposure by swallowing, skin contact or efects, reproductive or developmental toxicity. a review of triethanolamine-containing personal care products ine that could be present as an impurity in TEA or TEA-containing olamine available must be limited to the present practices of use g ingredients, are safe when formulated to be nonirritating and ascribed levels. These ingredients should not be used in cosmet A reported equivocal evidence of carcinogenic activity in male me evidence of carcinogenic activity in male rats based on ama. It has been hypothesized that TEA may cause liver tumours nuch less sensitive to this deficiency, and these hepatic findings the safety of the use of products formulated using TEA or TEA- ing these ingredients must be formulated using TEA or TEA- ing these ingredients must be formulated using TEA or TEA- ing these ingredients must be formulated using the safety of the use of products formulated using the norirritating. ting agents to directly form nitrosamines. However, tertiary dergoing nitrosative cleavage.he resultant secondary amine (ie, ay be carcinogenic. Because of the potential for this process to ed in cosmetic products in which N-nitroso compounds can be Containing Ingredients as Used in Cosmetics: International 01.4174&rep=rep1&type=pdf animal testing. tst one assay, or belongs to a family of chemicals producing		
COPPER SULFATE &	Asthma-like symptoms may continue for months or even yea	rs after exposure to the material ends. This may be due to a no		
BENZYL C12-14 ALKYLDIMETHYLAMMONIUM	allergic condition known as reactive airways dysfunction sync highly irritating compound. Main criteria for diagnosing RADS	drome (RADS) which can occur after exposure to high levels of S include the absence of previous airways disease in a non-atop		

CHLORIDE & individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe

ETHANOLAMINE 8 TRIETHANOLAMINE	bronchial hyperreactivity on methacholine ch eosinophilia. RADS (or asthma) following an	nallenge testing, and the lack of mi irritating inhalation is an infrequer	nimal lymphocytic inflammation, without nt disorder with rates related to the
	concentration of and duration of exposure to occurs as a result of exposure due to high co after exposure ceases. The disorder is chara	the irritating substance. On the ot oncentrations of irritating substance acterized by difficulty breathing, co	her hand, industrial bronchitis is a disorder that e (often particles) and is completely reversible ugh and mucus production.
ETHANOLAMINE 8 TRIETHANOLAMINE	Overexposure to most of these materials may Many amine-based compounds can cause re- effects, including constriction of the bronchi of include headache, nausea, faintness, anxiety urticaria (hives) and swelling of the face, whit There are generally four routes of possible oo Inhalation: Inhaling vapours may result in mo- lungs. Higher concentrations of certain amin nose, coughing, difficulty in breathing and ch- vomiting, drowsiness, sore throat, inflammatt prolonged exposure to some amines may re- shown to cause kidney, blood and central ne- While most polyurethane amine catalysts are and my experience distress while breathing, very small amounts of vapours. Once sensiti overexposure may lead to permanent lung in the bronchi, and immunologic lung disease. Products with higher vapour pressures may exposure. Inhalation hazards are increased when expo- heated vapours. Such situations include leaf exposure include asthma, bronchitis and em Skin contact: Skin contact with amine catalys severe irritation and injury, from simple reduc prolonged exposure may also result in sever allergic sensitization. Sensitised persons sho absorption of the amines though skin exposu pressure, reddening of the skin, hives, and fa the amines, and they are usually temporary. Eye contact: Amine catalysts are alkaline an contact with liquid amine may cause severe solid products may result in mechanical irrita Exposed persons may experience excessive which manifests as a blurred or foggy vision symptoms are temporary and usually disapp exposed to concentrations that do not cause Ingestion: Amine catalysts have moderate to burns of the mouth, throat, gullet and gastroi and the lungs. Affected people may also exp gastrointestinal tract, diarrhea, dizziness, dro The material may produce severe irritation to irritants may produce conjunctivitis. The material may cause skin irritation after p swelling, the production of vesicles, scaling a	ay cause adverse health effects. elease of histamines, which, in turn or asthma and inflammation of the y, a decrease in blood pressure, ra- ich are usually transient. In potential exposure: inhalation, sh- boderate to severe irritation of the ti- es can produce severe respiratory nest pain. Chronic exposure via inf- ion of the bronchi and lungs, and p sult in liver disorders, jaundice and revous system disorders in animal e not sensitisers, some certain ind including asthma-like attacks, who ized, these individuals must avoid hjury, including reduction in lung fu- reach higher concentrations in the essure to amine catalysts occurs in a suit in fitting or transfer lines. Medica physema. Its poses a number of concerns. It ess and swelling to painful blisterir re cumulative skin inflammation. Si- build avoid all contact with amine ca- ure may include headaches, nause acial swelling. These symptoms m d their vapours are irritating to the irritation and tissue injury, and the tion, pain and corneal injury. e tearing, burning, inflammation of with a blue tint, and sometimes a ear when exposure ends. Some p respiratory irritation. Intestinal tract. Material aspirated of powsiness, thirst, collapse of circula p the eye causing pronounced infla- mation and tissue injury.	n, can trigger allergic and other physiological cavity of the nose. Whole-body symptoms apid heartbeat, itching, reddening of the skin, sin contact, eye contact, and swallowing. ssues of the nose and throat and can irritate the irritation, characterized by discharge from the halation may cause headache, nausea, bossible lung damage. Repeated and/or d liver enlargement. Some amines have been studies. ividuals may also become sensitized to amines enever they are subsequently exposed to even any further exposure to amines. Chronic nction, breathlessness, chronic inflammation of air, and this increases the likelihood of worker situations that produce aerosols, mists or al conditions generally aggravated by inhalation Direct skin contact can cause moderate to ng, ulceration, and chemical burns. Repeated or kin contact with some amines may result in atalysts. Whole-body effects resulting from the ba, faintness, anxiety, decrease in blood ay be related to the pharmacological action of eyes, even at low concentrations. Direct "burning" may lead to blindness. Contact with the conjunctiva, and swelling of the cornea, halo phenomenon around lights. These eople may experience this effect even when e amines can cause severe irritation, ulcers and due to vomiting can damage the bronchial tubes nen, nausea, bleeding of the throat and tion, coma and even death. ammation. Repeated or prolonged exposure to ad may produce on contact skin redness,
Acute Toxicity	~	Carcinogenicity	¥
Skin Irritation/Corregion		Benroductivity	×

Acute Toxicity	×	Carcinogenicity	✓
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	*	STOT - Single Exposure	*
Respiratory or Skin sensitisation	*	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
	Le	gend: 🛛 🗙 – Data either not ava	ilable or does not fill the criteria for classification

Data available to make classification

SECTION 12 Ecological information

Toxicity

Not Available	Not Available	Not	Not
	Not Available	Available	Available
t Test Duration (hr)	Species	Value	Source
72h	Algae or other aquatic plants	<0.001mg/L	4
96h	Algae or other aquatic plants	0.011mg/L	4
in	int Test Duration (hr) 72h 96h	IntTest Duration (hr)Species72hAlgae or other aquatic plants96hAlgae or other aquatic plants	IntTest Duration (hr)SpeciesValue72hAlgae or other aquatic plants<0.001mg/L

	NOEC(ECx)	384h		Fish	<0	.001mg/L	4
	EC50	48h		Crustacea	0.0	01mg/L	2
	LC50	96h		Fish	<0	.001mg/L	4
	Endpoint	Test Duration (hr)	5	Species	Valu	ie	Sourc
	EC50	72h	ļ	Algae or other aquatic plants	0.01	4mg/L	2
benzyl C12-14	EC50	96h	1	Algae or other aquatic plants	~0.0)2mg/l	2
alkyldimethylammonium chloride	EC50	48h	(Crustacea	0.01	6mg/l	2
	NOEC(ECx)	72h	1	Algae or other aquatic plants	<=0	.001mg/L	2
	LC50	96h	F	Fish	0.28	smg/l	2
	Endpoint	Test Duration (hr)		Species		Value	Sourc
	EC50	96h		Algae or other aquatic plants		80mg/l	2
	EC50	72h		Algae or other aquatic plants		15mg/l	1
ethanolamine	NOEC(ECx)	72h		Algae or other aquatic plants 4mg/l		4mg/l	1
	EC50	48h		Crustacea		65mg/l	1
	LC50	96h		Fish		75mg/l	1
	Endpoint	Test Duration (hr)	S	pecies	Value	•	Sourc
	EC50	96h	A	lgae or other aquatic plants	169m	ng/l	1
	BCF	1008h	F	ïsh	<0.4		7
triethanolamine	EC50	72h	Algae or other aquatic plants		>107	<260mg/l	2
thethanolamine	NOEC(ECx)	Not Available	Fish		>1mg/l		2
	EC50	48h	Crustacea		565.2- 658.3mg/l		4
		1					

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
copper sulfate	HIGH	HIGH
ethanolamine	LOW	LOW
triethanolamine	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
copper sulfate	LOW (BCF = 3.162)
benzyl C12-14 alkyldimethylammonium chloride	LOW (LogKOW = 2.93)
ethanolamine	LOW (LogKOW = -1.31)
triethanolamine	LOW (BCF = 3.9)

Mobility in soil

Ingredient	Mobility
copper sulfate	LOW (Log KOC = 6.124)
ethanolamine	HIGH (Log KOC = 1)
triethanolamine	LOW (Log KOC = 10)

SECTION 13 Disposal considerations

	Containers may still present a chemical bazard/ danger when empty.
	Solitations may suit present a chemical nazaru danger when empty.
	Return to supplier for reuse/ recycling if possible.
	Otherwise:
	If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to
	store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
	Where possible retain label warnings and SDS and observe all notices pertaining to the product.
Product / Packaging	DO NOT allow wash water from cleaning or process equipment to enter drains.
disposal	It may be necessary to collect all wash water for treatment before disposal.
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
	Where in doubt contact the responsible authority.
	Recycle wherever possible or consult manufacturer for recycling options.
	 Consult State Land Waste Authority for disposal.
	 Bury or incinerate residue at an approved site.
	Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant	
HAZCHEM	•3Z

Land transport (ADG)

14.1. UN number or ID number	3082	
14.2. UN proper shipping name	ENVIRONMENTALLY alkyldimethylammoniu	HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains copper sulfate and benzyl C12-14 m chloride)
14.3. Transport hazard class(es)	Class Subsidiary Hazard	9 Not Applicable
14.4. Packing group	Ш	
14.5. Environmental hazard	Environmentally hazar	dous
14.6. Special precautions for user	Special provisions Limited quantity	274 331 335 375 AU01 5 L

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in;

(a) packagings;

(b) IBCs; or

(c) any other receptacle not exceeding 500 kg(L).

- Australian Special Provisions (SP AU01) - ADG Code 7th Ed.

Air transport (ICAO-IATA / DGR)

14.1. UN number	3082			
14.2. UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains copper sulfate and benzyl C12-14 alkyldimethylammonium chloride)			
14.3. Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subsidiary Hazard ERG Code	9 Not Applicable 9L		
14.4. Packing group	Ш			
14.5. Environmental hazard	Environmentally hazardous			
14.6. Special precautions for user	Special provisions		A97 A158 A197 A215	
	Cargo Only Packing Instructions		964	

Cargo Only Maximum Qty / Pack	450 L
Passenger and Cargo Packing Instructions	964
Passenger and Cargo Maximum Qty / Pack	450 L
Passenger and Cargo Limited Quantity Packing Instructions	Y964
Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3082			
14.2. UN proper shipping name	ENVIRONMENTALLY alkyldimethylammoniu	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains copper sulfate and benzyl C12-14 alkyldimethylammonium chloride)		
14.3. Transport hazard class(es)	IMDG Class IMDG Subsidiary Ha	9 azard Not Applicable		
14.4. Packing group	Ш	III		
14.5 Environmental hazard	Marine Pollutant			
14.6. Special precautions for user	EMS Number Special provisions Limited Quantities	F-A , S-F 274 335 969 5 L		

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
copper sulfate	Not Available
benzyl C12-14 alkyldimethylammonium chloride	Not Available
ethanolamine	Not Available
triethanolamine	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
copper sulfate	Not Available
benzyl C12-14 alkyldimethylammonium chloride	Not Available
ethanolamine	Not Available
triethanolamine	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

I.	copper sulfate is found on the following regulatory lists	
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	
	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4	
	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5	
	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6	
	Australian Inventory of Industrial Chemicals (AIIC)	
benzyl C12-14 alkyldimethylammonium chloride is found on the following regulatory lists		
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	
	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5	

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

ethanolamine is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4	
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5	
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6	
Australian Inventory of Industrial Chemicals (AIIC)	

triethanolamine is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (copper sulfate; benzyl C12-14 alkyldimethylammonium chloride; ethanolamine; triethanolamine)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	TSCA Inventory 'Active' substance(s) (copper sulfate; ethanolamine; triethanolamine); No (benzyl C12-14 alkyldimethylammonium chloride)
Taiwan - TCSI	Yes
Mexico - INSQ	No (benzyl C12-14 alkyldimethylammonium chloride)
Vietnam - NCI	Yes
Russia - FBEPH	No (benzyl C12-14 alkyldimethylammonium chloride)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	06/10/2023
Initial Date	29/09/2023

Other information

Ingredients with multiple cas numbers

Name	CAS No
copper sulfate	7758-98-7, 23254-43-5
benzyl C12-14 alkyldimethylammonium chloride	85409-22-9, 85409-23-0
ethanolamine	141-43-5, 2122854-11-7, 9007-33-4

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit.
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.